

# TS72

## Heavy duty floor repair and screed



### Benefits of TS72?

Ease of application .  
**Can be used as a levelling or a repair system.**  
 Low odour, safe to install into food preparation areas.  
**Hard wearing durable floor for industrial use.**  
 Good slip-resistance properties.  
**Excellent abrasion and impact resistance.**

### What is TS72?

TS72 is a heavy duty, epoxy floor screed, with high chemical resistance. TS72 is applied by a trowel and once fully cured has a compressive strength of 80N/mm<sup>2</sup>. TS72 is suitable for use on almost any area that requires a high quality repair solution due to its ability to bond to with any substrate.

### Recommended Uses

Chemical production and storage  
**Printing and packaging areas**  
 Engineering facilities  
**Automotive**  
 Industrial workshops

Use TS72 on floors, bund walls anywhere that requires a strong finish.

### Application

**Preparation:** to achieve the best results with TS72, the substrate should be clean sound and dry.

**Priming:** TS72 primer, mix the base and hardener together. TS72 can be applied on to a wet coat of TS72 primer, very rough or porous surfaces may require an extra coat of primer, the first coating should be allowed to dry before applying the wet coat.

**Application:** TS72 base should be premixed to create a uniform colour, the base and hardener should then be completely mixed at a slow speed and then the aggregate added slowly. The complete mix should be spread evenly and compacted on to the floor, the ambient temp should not fall below 10°C and the substrate temp should not be below 5°C.

### Health and Safety

Always ensure that precautionary measures found in the MSDS sheet for TS72 are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.

### Technical Data

<b>Pack size</b>	22kg (5 part Kit)
<b>Coverage</b>	2 sqm at 6mm depth
<b>Temperature resistance</b>	60°C
<b>Chemical resistance</b>	good
<b>Pot life</b>	30 mins
<b>Drying time</b>	
	24 hours light traffic
	72 hours full traffic
	7 days full chemical cure
<b>Compressive strength</b>	80N/mm <sup>2</sup>
<b>Flexural strength</b>	20N/mm <sup>2</sup>
<b>Tensile strength</b>	20N/mm <sup>2</sup>

**TEROTECH** Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.  
 Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

**Trademarks:** **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

