

Framesaver

An advanced penetrating polymer



An advanced penetrating polymer wood repair and filling solution for professional use

What is New Framesaver?

Framesaver is a pre-coloured, 2 part, high strength, polyester wood filler. It provides a strong, high quality repair which penetrates deeply into rotten or damaged wood. Framesaver is perfect for wood imperfections, particularly corner work and deep holes up to 50mm such as wood knots.

How does Framesaver Work?

Framesaver is a 2 part product, that when mixed, will cure to form a polymer wood repair. Framesaver builds the wooden surface up to its original level which can then be trimmed, sanded, stained and painted to match the original wood flawlessly.

Key Features and Benefits of Framesaver?

Durable repair - forms a strong and durable bond.

Economical to use and re-use, no waste.

Weatherproof - suitable for exterior or interior use.

Paintable and stainable, just like wood.

Repairs and reinforces window frames, furniture, doors, bannisters and more.

Easy to sand down to perfection. Professional grade.

Instructions for Use

Preparation

Prior to application, all surfaces should be clean, dry, sound and free from oil or grease. On old timber, any rotten or weak areas should be cut back to solid timber. Smooth areas should be slightly abraded to ensure a good key is obtained.

Mixing

Framesaver should be mixed in the proportion of 50 parts of base, to 1 part of hardener (a golf ball volume of base to 1.5 inch of hardener). As Framesaver is a fast curing filler, it is recommended that only small quantities are mixed at a time – enough to be applied within 5 minutes of mixing.

To mix, simply add the hardener to the paste on a suitable board. Mixing should be carried out by spatula or stiff knife until a smooth, even coloured mix is obtained. Ensure that the filler is scraped clear of the mixing board at least once. This ensures that all the filler is mixed with the hardener and no uncured material will therefore be used.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.





Framesaver

An advanced penetrating polymer



Application

Apply Framesaver using a putty knife, spatula or similar, directly to the area of timber to be repaired. Shape the product as required with a spreader or flat former. Leave enough excess proud of the surface to allow for sanding. For deep filling it may be necessary to build the product up in layers. Allow Framesaver to cure before sanding, painting, staining etc. It is important that the total surface of the repair is fully sanded to ensure that the stain or finish can fully penetrate. Trials are recommended on an inconspicuous area prior to full scale repair to ensure suitability.

Technical Information

Gelling Time

Framesaver's typical gelling time is around 10 minutes at 15°C and reaches full strength after just 30 minutes. The amount of hardener used, as well as the overall volume of mixed material and ambient temperature will all affect gelling times.

Storage

Framesaver should be stored between 5°C and 25°C and has a shelf life of 12 months.

Health and Safety

Before use, it is important that you have read the Safety Data Sheet in its entirety and the appropriate PPE is worn during use.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

