

TT005

A multi-purpose, flexible waterproofing and sealant solution



A multi-purpose, flexible waterproofing and sealant solution for all types of surfaces

What is New TT005?

TT005 is a high performance, easily applied elastomeric sealant that is perfect for waterproofing or bonding critical movement gaps between nearly all roofing and construction materials. It can be used to bond or repair guttering, bedding roof fixtures, movement or expansion joints and even manhole perimeter joints.

How does TT005 Work?

TT005 is a unique formulation that offers all the advantages of both bitumen and natural rubber. It will seal nearly any gap between brickwork, concrete, metals, plastics, and glass. It has an amazing 700% elasticity at 24oC, with a recovery of 96%.

It performs well in temperatures between -40oC and a blistering 80oC, and offers exceptional adhesive strength.

Key Features and Benefits of TT005?

Fast and easy gun application
Excellent adhesion to almost any surface

Non slumping, yet highly elastic – perfect for bonds subject to movement

Can be applied at temperatures between -5oC and 50oC, and works well between -30oC and 80oC

Resistant to alkalis and acids
Offers long term durability

Technical Information

TT005 is gun-applied, and is slump free in vertical joints up to 20mm * 20mm. It is suitable for any kind of sealing and waterproofing, especially movement and expansion joints. TT005 cures within 48 hours of application.

Coverage per 310ml cartridge:

3mm * 3mm joint	34.0 metres
6mm * 3mm	16.7m
6mm * 6mm	8.3m
9mm * 9mm	3.8m
12mm * 6mm	4.2m
15mm * 6mm	3.3m
15mm * 15mm	1.3m

For your protection, always read the MSDS sheet for TT005 before use and follow it closely.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

