



Extreme Bond Part B

A 2-part toughened structural acrylic for bonding

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



SECTION 1

Product name
Product Use

PRODUCT IDENTIFICATION

Extreme Bond (Part B)
Adhesive



SECTION 2

Classification 1272/2008/EC

HAZARDS IDENTIFICATION

Physical and Chemical Hazards
Human health

Flam. Liq. 2: H225

Sk. Irrit.2: H315; Sk. Sens.1: H317; Eye Damage 1: H318;

STOT SE3: H335

Not classified

Environment

Danger

Contains: Methyl methacrylate, 2-hydroxyethyl methacrylate, methacrylic acid.

Signal word:
Hazard
statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary
statements:

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P310 Immediately call a POISON CENTRE/Doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.



SECTION 3

Hazardous components

Chemical Name(s)

Methyl methacrylate

2-hydroxyethyl methacrylate

Methacrylic acid

COMPOSITION

Related Information

% (w/w)

25-50%

10-25%

1-5%

CAS no.

80-62-6

868-77-9

79-41-4

Classification

Flam. Liq.2

Skin Irrit.2

Skin Sens.1

STOT SE3

Skin Irrit.2

Skin Sens.1

Eye Irrit.2

Skin Corr.1A

Acute Tox.4

H-Statements

H225

H315

H317

H335

H315

H317

H319

H314

H302, H312

SECTION 4

In cases of contact

Eyes

Ingestion

Inhalation

Skin

FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.

Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet.

Remove to fresh air for at least 10 minutes.

Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream.

Seek medical advice if irritation develops.

	<p>SECTION 5 Extinguishing media Special procedures</p>	<p>FIRE FIGHTING MEASURES Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet. Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.</p>
	<p>SECTION 6 Clean-up procedures</p>	<p>ACCIDENTAL RELEASE MEASURES Remove all ignition sources. Do not discharge into drains or rivers. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.</p>
	<p>SECTION 7 Handling Storage</p>	<p>HANDLING AND STORAGE Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work. Store in a cool, well ventilated area. Keep containers tightly closed.</p>
	<p>SECTION 8 Hazardous components Chemical name Methyl methacrylate Methacrylic acid Engineering measures Respiratory protection Hand protection Eye protection Skin protection</p>	<p>EXPOSURE CONTROLS AND PERSONAL PROTECTION Workplace exposure limits (WELs) 8 hour TWA 15 min STEL Related information 50 ppm 100ppm 20 ppm 40 ppm Ensure there is sufficient ventilation of the area. If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required. Protective gloves. Wear safety glasses if there is a risk of eye contact. Protective overalls.</p>
	<p>SECTION 9 State: Liquid Colour: Pink</p>	<p>PHYSICAL AND CHEMICAL PROPERTIES Odour: Characteristic Dynamic viscosity: 3000 mPas S.G. 1.01 Boiling Pt.: 101°C Flash point °C: 10 Autoflammability: 430°C Solubility: Immiscible in water</p>
	<p>SECTION 10 Stability Conditions to avoid Materials to avoid Decomposition products</p>	<p>STABILITY AND REACTIVITY Stable under normal conditions. Hot surfaces. Sources of ignition. Flames. Strong oxidising agents. Strong acids. Combustion will generate oxides of carbon, acrid smoke and irritating fumes.</p>
	<p>SECTION 11 Hazardous ingredients: Routes of exposure:</p>	<p>TOXICOLOGICAL INFORMATION Methyl methacrylate, ORL MUS LD50 3625 mg/kg, ORL RAT LDLO 7872 mg/kg Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases. May cause an allergic skin reaction. May cause serious eye damage.</p>
	<p>SECTION 12</p>	<p>ECOLOGICAL INFORMATION Should not be discharged directly in concentrated form to water courses.</p>
	<p>SECTION 13 Disposal operations NB: The user's attention is drawn to</p>	<p>DISPOSAL CONDITIONS Contact licensed waste disposal company. the possible existence of regional or national regulations regarding disposal.</p>
	<p>SECTION 14 UN no: 1133 Shipping name: Adhesives</p>	<p>TRANSPORT INFORMATION Class: 3 PG: II Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 33 IMDG/IMO EmS: F-E,S-D IATA/ICAO Packing Instructions: 351 (P&CA) Tariff Number: 35069100</p>
	<p>SECTION 15 Regulatory references:</p>	<p>REGULATORY INFORMATION Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.</p>
	<p>SECTION 16</p>	<p>OTHER INFORMATION N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office. Always use in accordance with manufacturer's directions. Dated 05/12/16 CLP/Rev.1</p>

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

